



# NTK BEARING PRECISION AXLE CORP.



1.181 Inch | 30 Millimeter x 2.165 Inch | 55 Millimeter x 1.024 Inch | 26 Millimeter SKF 7006 CE/DBAVQ126 Angular Contact Ball Bearings

Bearing No. 7006 CE/DBAVQ126

7006 CE/DBAVQ126 Bearing 2D drawings and 3D CAD models

|                                 |  |
|---------------------------------|--|
| Category                        | Angular Contact Ball Bearings  |
| Inventory                       | 0.0  |
| Manufacturer Name               | SKF  |
| Minimum Buy Quantity            | N/A  |
| Weight                          | 0  |
| Product Group                   | B04270   |
| Enclosure                       | Open   |
| Flush Ground                    | Yes  |
| Rolling Element                 | Ball Bearing   |
| Number of Rows of Balls         | Single Row   |
| Precision Class                 | ABEC 1   ISO P0  |
| Maximum Capacity / Filling Slot | No   |
| Snap Ring                       | No   |
| Cage Material                   | Phenolic   |
| Contact Angle                   | 15 Degree  |
| Internal Clearance              | C0-Medium  |
| Number of Bearings              | 2 (1 Pair)   |
| Preload                         | Light  |
| Mounting Arrangement            | Duplex-Back to Back  |
| Inch - Metric                   | Metric   |
| Long Description                | 30MM Bore; 55MM Outside Diameter; 26MM Width; Open; Yes Flush Ground; Ball Bearing; Single |



## NTK BEARING PRECISION AXLE CORP.

|                        |   |
|------------------------|---|
|                        | Row of Balls; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; C0-Medium; Phenolic Cage; 15 Degree; 2 (1 Pair) |
| Other Features         | High Speed Design   |
| Category               | Angular Contact Ball Bearing  |
| UNSPSC                 | 31171531  |
| Harmonized Tariff Code | 8482.10.50.28   |
| Noun                   | Bearing   |
| Keyword String         | Angular Contact   |
| Manufacturer URL       | <a href="http://www.skf.com">http://www.skf.com</a>   |
| d                      | 1.181 Inch   30 Millimeter  |
| B                      | 1.024 Inch   26 Millimeter  |
| D                      | 2.165 Inch   55 Millimeter  |