



# NTK BEARING PRECISION AXLE CORP.

2.5 Inch | 63.5 Millimeter x 3.5 Inch | 88.9 Millimeter x 2.75 Inch | 69.85 Millimeter LINK BELT PKEB22440H Pillow Block Bearings



Bearing No. PKEB22440H

PKEB22440H Bearing 2D drawings and 3D CAD models

|                           |   |
|---------------------------|---|
| Category                  | Pillow Block Bearings   |
| Inventory                 | 0.0   |
| Manufacturer Name         | REXNORD   |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 8.17  |
| EAN                       | 0662327115272   |
| Product Group             | M06288  |
| Number of Mounting Holes  | 2   |
| Mounting Method           | Concentric Collar   |
| Housing Style             | 2 Bolt Pillow Block   |
| Rolling Element           | Spherical Roller Bearing  |
| Housing Material          | Cast Steel  |
| Expansion / Non-expansion | Expansion   |
| Mounting Bolts            | 5/8 Inch  |
| Relubricatable            | Yes   |
| Insert Part Number        | B22440HL  |
| Seals                     | Floating Labyrinth  |
| Housing Configuration     | 1 Piece Solid   |
| Inch - Metric             | Inch  |
| Other Features            | Double Row   Single Collar   Extended Inner Race   With Set Screw   |
| Long Description          | 2 Bolt Pillow Block; 2-1/2" Bore; 2-3/4" Base to Center Height; Concentric Collar Mount; Spherical Roller |



## NTK BEARING PRECISION AXLE CORP.

|                                  |  |
|----------------------------------|--|
|                                  | Bearing; Relubricatable;<br>Cast Steel; Floating<br>Labyrinth; Expansion |
| Category                         | Pillow Block   |
| UNSPSC                           | 31171511   |
| Harmonized Tariff Code           | 8483.20.40.80  |
| Noun                             | Bearing  |
| Keyword String                   | Pillow Block   |
| Manufacturer URL                 | <a href="http://www.rexnord.com">http://www.rexnord.com</a>              |
| Manufacturer Item Number         | PKEB22440H   |
| Manufacturer Internal<br>Number  | 5811527  |
| Weight / LBS                     | 18   |
| D                                | 3.5 Inch   88.9 Millimeter   |
| B                                | 2.75 Inch   69.85 Millimeter   |
| Bolt Spacing Maximum             | 0 Inch   0Millimeter   |
| d                                | 2.5 Inch   63.5 Millimeter   |
| Nominal Bolt Center to<br>Center | 7.1 Inch   181 Millimeter  |
| Bolt Spacing Minimum             | 0 Inch   0Millimeter   |
| Actual Bolt Center to<br>Center  | 7.1 Inch   181Millimeter   |